

**ELECTRICAL CHARACTERISTICS (designed to IEC standards):**

<b>% of Amp Rating</b>	<b>53 Series</b>	<b>52 Series</b>	<b>50 Series</b>
150%	1 hour Minimum	1 hour Minimum	1 hour Minimum
210 %	30 minutes Maximum	2 minutes (0.08-1.25A) 30 minutes (.6-10A) Maximum	2 minutes (0.08-1.25A) 30 minutes (.6-10A) Maximum
400%	0.3 secs. Maximum	0.15-0.8 secs. (0.08-1.25A) 0.2-2 secs. (1.6-10A)	0.3-2 secs. (0.08-1.25A) 0.3-3 secs. (1.6-10A)
1000%	0.02 secs. Maximum		

<i>5mm X 20mm</i>				
<i>Fast-Acting</i>	<i>Semi-Slow</i>	<i>Slow-Blow</i>		
<b>Part-No</b>	<b>Part-No</b>	<b>Part-No</b>	<b>Amp</b>	<b>Voltage</b>
53-0.08	52-0.08	50-0.08	80 mA	250 V
53-0.1	52-0.1	50-0.1	0.1	250 V
53-0.125	52-0.125	50-0.125	0.125	250 V
53-0.16	52-0.16	50-0.16	0.16	250 V
53-0.2	52-0.2	50-0.2	0.2	250 V
53-0.25	52-0.25	50-0.25	0.25	250 V
53-0.315	52-0.315	50-0.315	0.315	250 V
53-0.4	52-0.4	50-0.4	0.4	250 V
53-0.5	52-0.5	50-0.5	0.5	250 V
53-0.63	52-0.63	50-0.63	0.63	250 V
53-0.8	52-0.8	50-0.8	0.8	250 V
53-1	52-1	50-1	1	250 V
53-1.25	52-1.25	50-1.25	1.25	250 V
53-1.6	52-1.6	50-1.6	1.6	250 V
53-2	52-2	50-2	2	250 V
53-2.5	52-2.5	50-2.5	2.5	250 V
53-3	52-3	50-3	3	250 V
53-4	52-4	50-4	4	250 V
53-5	52-5	50-5	5	250 V
53-6.3	52-6.3	50-6.3	6.3	250 V
53-8	52-8	50-8	8	250 V
53-10	52-10	50-10	10	250 V