

**ELECTRICAL CHARACTS.**

| <b>% of Amp Rating</b> | <b>Opening Time</b>                    |
|------------------------|--|
| 110%                   | 4 hrs, Min                             |
| 135%                   | 1 hr, Max                              |
| 200%                   | 5 sec, Max<br><b>(glass body)</b>      |
| 200%                   | 15 sec, Max<br><b>(ceramic, 1-10A)</b> |
| 200%                   | 60 sec, Max<br><b>(ceramic,15-30A)</b> |

| <i>Fast Acting, 1/4" X 1 1/4", 250V</i> |             |                     |             |
|---|-------------|---------------------|-------------|
| <b>Glass Body</b>                       |             | <b>Ceramic Body</b> |             |
| <b>Part. No.</b>                        | <b>Amp.</b> | <b>Part. No.</b>    | <b>Amp.</b> |
| 04-0.01                                 | 10 mA       | 14-1                | 1           |
| 04-0.02                                 | 20 mA       | 14-2                | 2           |
| 04-0.032                                | 32 mA       | 14-3                | 3           |
| 04-0.063                                | 63 mA       | 14-4                | 4           |
| 04-0.080                                | 80 mA       | 14-5                | 5           |
| 04-0.1                                  | 0.1         | 14-6                | 6           |
| 04-0.125                                | 0.125       | 14-7                | 7           |
| 04-0.2                                  | 0.2         | 14-8                | 8           |
| 04-0.25                                 | 0.25        | 14-10               | 10          |
| 04-0.3                                  | 0.3         | 14-15               | 15          |
| 04-0.4                                  | 0.4         | 14-20               | 20          |
| 04-0.6                                  | 0.6         | 14-30               | 30          |
| 04-0.75                                 | 0.75        |                     |             |
| 04-1                                    | 1           |                     |             |
| 04-1.25                                 | 1.25        |                     |             |
| 04-1.5                                  | 1.5         |                     |             |
| 04-2                                    | 2           |                     |             |
| 04-2.5                                  | 2.5         |                     |             |
| 04-3                                    | 3           |                     |             |
| 04-4                                    | 4           |                     |             |
| 04-5                                    | 5           |                     |             |
| 04-6                                    | 6           |                     |             |
| 04-8                                    | 8           |                     |             |
| 04-10                                   | 10          |                     |             |